

ETCO (FLL-ETCO-12) CONNECTIONS

ETCO connectors are simple to attach to a FLATLITE lamp using pliers and a press. Anything that applies smooth, even, parallel pressure of about 500 p.s.i. will work, such as a 1/2 ton Arbor Press.



Arbor Press



Pair of ETCO connectors with 12" (30cm) leads (FLL-ETCO-12)

NOTE: Use one pair of connectors for every 5000 square inches (32K square cm) of lamp. For example, a 12,500 square inch (80K square cm) lamp should have 6 connectors: 3 on each side of the scribe line.

1) Seal the edge of lamp that is to receive the connectors (if not already sealed) using clear tape. E-Lite recommends Scotch® Premium Transparent Film Tape 600 Clear - 3M Part Number : 06941 or similar.



2) Attach one ETCO on either side of the scribe line and set them with standard pliers or vise-grips. The back of the ETCO (where leads are attached) should be on the back of the lamp.



3) Firmly affix the ETCO connectors to the lamp using 1/2 Ton Arbor Press or similar.



4) Insulate connectors using E-Lite connector sealing tape FLT-0075W-3 or similar. A shock hazard exists until the lamp edges are sealed and the connectors are insulated.



"It's not Neon...it's better!"

1040 Avenida Acaso, Camarillo, CA 93012

Phone: (800) 336-6500 ext. 519 Fax: (805) 388-7950

Email: info@californeon.com Website: <http://www.californeon.com>